

B1

1. (Currently Amended) A method for outputting a performance, comprising:
receiving broadcast performance information via a network;
composing the performance by mixing [stored] information stored on a local storage device with one or more portions of the received broadcast performance information; and
outputting the performance.

2. (Original) The method of claim 1, further comprising:
recording the performance information; and
outputting a second performance using the recorded performance information as stored information.

3. (Original) The method of claim 1, the composing the performance comprising:
retrieving one or more commands from the performance information;
decoding the one or more commands; and
performing one or more tasks instructed by the commands.

4. (Original) The method of claim 3, wherein performing the one or more tasks comprises executing a macro.

5. (Original) The method of claim 4, wherein executing the macro comprises:
retrieving the macro based on the decoded one or more commands;
decoding the macro to generate a macro command sequence; and
executing the macro command sequence.

6. (Original) The method of claim 5, wherein executing the respective commands comprises one or more of:
generating a sequence of commands for outputting the performance; and
assembling one or more stored command sequences for outputting the performance.

7. (Original) The method of claim 5, wherein executing the macro command sequence comprises:

retrieving audio and/or video synthesis information;
retrieving information indicating desired output content; and
generating synthesized performance information based on the audio and/or video synthesis information and the information indicating the desired output content.

8. (Original) The method of claim 3, wherein performing the one or more tasks comprises reproducing a real-time transmission included in the performance information.

9. (Original) The method of claim 3, further comprising:

executing programming commands;
generating a sequence of commands based on the executed programming commands; and
incorporating the decoded commands into the sequence of commands.

10. (Original) The method of claim 9, wherein incorporating the decoded commands includes adding onto, interrupting, switching or replacing one or more commands within the sequence of commands, and the one or more portions of the performance are added onto, interrupted, switched or replaced based upon the incorporated decoded commands.

11. (Original) The method of claim 3, wherein performing one or more tasks comprises:

retrieving audio and/or video synthesis information;
retrieving information indicating desired output content; and
generating synthesized performance information based on the audio and/or video synthesis information and the information indicating the desired output content.

12. (Original) The method of claim 3, wherein the one or more commands includes one or more of programming commands that execute a software program, housekeeping commands that load, delete, change or overlay stored information, and performance commands that instruct to reproduce stored information from one or more specified

locations of a storage device.

13. (Previously Withdrawn)

14. (Previously Withdrawn)

15. (Previously Withdrawn)

16. (Previously Withdrawn)

B1
17. (Previously Withdrawn)

18. (Currently Amended) A pseudo-live performance output device, comprising:

a controller that receives broadcast performance information via a network and composes the performance by mixing [stored] information stored on a local storage device with one or more portions of the received broadcast performance information; and an output device that outputs the performance.

19. (Original) The pseudo-live performance output device of claim 18, further comprising a recording device that records the performance information, wherein the output device outputs a second performance using the recorded performance information as stored information.

20. (Original) The pseudo-live performance output device of claim 18, wherein the controller:

retrieves one or more commands from the performance information;
decodes the one or more commands; and
performs one or more tasks instructed by the commands.

21. (Original) The pseudo-live performance output device of claim 20, wherein performing the one or more tasks comprises executing a macro.

22. (Original) The pseudo-live performance output device of claim 21, wherein executing the macro comprises:

retrieving the macro based on the decoded one or more commands;
decoding the macro to generate a macro command sequence; and
executing the macro command sequence.

23. (Original) The pseudo-live performance output device of claim 22, wherein executing the macro command sequence comprises one or more of:

B1
generating a sequence of commands for outputting the performance; and
assembling one or more stored command sequences for outputting the performance.

24. (Original) The pseudo-live performance output device of claim 22, wherein executing the macro command sequence comprises:

retrieving audio and/or video synthesis information;
retrieving information indicating desired output content; and
generating synthesized performance information based on the audio and/or video synthesis information and the information indicating the desired output content.

25. (Original) The pseudo-live performance output device of claim 20, wherein performing the one or more tasks comprises reproducing a real-time transmission included in the performance information.

26. (Original) The pseudo-live performance output device of claim 20, wherein the controller:

executes programming commands;
generates a sequence of commands based on the executed programming commands; and
incorporates the decoded commands into the sequence of commands.

27. (Original) The pseudo-live performance output device of claim 26, wherein

incorporating the decoded commands includes adding onto, interrupting, switching or replacing one or more commands within the sequence of commands, and the one or more portions of the performance are added onto, interrupted, switched or replaced based upon the incorporated decoded commands.

28. (Original) The pseudo-live performance output device of claim 20, wherein performing one or more tasks comprises:

retrieving audio and/or video synthesis information;
retrieving information indicating desired output content; and
B1
generating synthesized performance information based on the audio and/or video synthesis information and the information indicating the desired output content.

29. (Original) The pseudo-live performance output device of claim 20, wherein the one or more commands include one or more of programming commands that execute a software program, housekeeping commands that load, delete, change or overlay stored information, and performance commands that instruct to reproduce stored information from one or more specified locations of a storage device.

30. (Previously Withdrawn)

31. (Previously Withdrawn)

32. (Previously Withdrawn)
